

Experimental Validation of an Enhanced System Synthesis Approach

Lena C. Altherr, Thorsten Ederer, Ulf Lorenz, Peter Pelz, Philipp Pöttgen

Abstract Planning the layout and operation of a technical system is a common task for an engineer. Typically, the workflow is divided into consecutive stages: First, the engineer designs the layout of the system, with the help of his experience or of heuristic methods. Secondly, he finds a control strategy which is often optimized by simulation. This usually results in a good operating of an unquestioned system topology. In contrast, we apply Operations Research (OR) methods to find a cost-optimal solution for both stages simultaneously via mixed integer programming (MILP). Technical Operations Research (TOR) allows one to find a provable global optimal solution within the model formulation. However, the modeling error due to the abstraction of physical reality remains unknown. We address this ubiquitous problem of OR methods by comparing our computational results with measurements in a test rig. For a practical test case we compute a topology and control strategy via MILP and verify that the objectives are met up to a deviation of 8.7%.

Acknowledgements This work is partially supported by the German Federal Ministry for Economic Affairs and Energy funded project “Entwicklung hocheffizienter Pumpensysteme” and by the German Research Foundation (DFG) funded SFB 805.

Lena C. Altherr
Chair of Fluid Systems, TU Darmstadt e-mail: lena.altherr@fst.tu-darmstadt.de

Thorsten Ederer
Discrete Optimization, TU Darmstadt e-mail: ederer@mathematik.tu-darmstadt.de

Ulf Lorenz
Chair of Fluid Systems, TU Darmstadt e-mail: ulf.lorenz@fst.tu-darmstadt.de

Peter F. Pelz
Chair of Fluid Systems, TU Darmstadt e-mail: peter.pelz@fst.tu-darmstadt.de

Philipp Pöttgen
Chair of Fluid Systems, TU Darmstadt e-mail: philipp.poettgen@fst.tu-darmstadt.de

1 Introduction

Mixed-integer linear programming (MILP) [4] is the outstanding modeling technique for computer-aided optimization of real-world problems, e.g. logistics, flight or production planning. Regarding the successful application in other fields, it is desirable to transfer Operations Research (OR) methods to the optimization of technical systems.

The design process of a technical system is typically divided into two consecutive stages: First, the engineer designs the layout of the system, with the help of his experience or of heuristic methods. Secondly, he finds a control strategy which is often optimized by simulation. This usually results in a good operating of an unquestioned system topology.

In order to provide engineers with a methodical procedure for the design of new technical systems, we strive to establish Technical Operations Research (TOR) in engineering sciences. The TOR approach allows one to find an optimal solution for both the topology decision and the usage strategy simultaneously via MILP [3]. While this formulation enables us to prove global optimality and to assess feasible solutions using the global optimality gap, the modeling error often cannot be quantified.

Our aim in this paper is to quantify the modelling error for a MILP of a booster station with accumulators based on [2] and [1]. We examine a practical test case and compare the computed results with measurements in a test rig.

2 Problem Description

We replicate MILP predictions for the topology and operating of a technical system in a test rig and compare the computed optimal solution to experimental results. A manageable test case is a water-conveying system, in which a certain amount of water per time has to be pumped from the source to the sink. Such a time-dependent volume flow demand can for example be observed when people shower in a multi-story building. To fulfill this time-varying load, a system designer may choose one single speed-controlled pump dimensioned to meet the peak demand.

Another option is a booster station. It consists of an optional accumulator and a set of pumps which are able to satisfy the peak load in combined operation. Compared to the single pump, this set-up allows for a more flexible operating that may lead to lower energy consumption. The speed of each active pump can be adjusted according to the demand, so that they may operate near their optimal working point and thus with higher efficiency. The designer's challenging task is to trade off investment costs and energy efficiency while considering all possible topology and operating options.

3 Mixed Integer Linear Program

Our model consists of two stages: First, find a low-priced investment decision in an adequate set of pumps, pipes, accumulators and valves. Secondly, find energy-optimal operating settings for the selected components. The goal is to compare all

possible systems that fulfill the load and to minimize the sum of investment and energy costs over a given depreciation period.

All possible systems can be modelled by a graph $G = (V, E)$ with edges E corresponding to possible components, and vertices V representing connection points between these components. A binary variable $p_{i,j}$ for each optional component $(i, j) \in V$ indicates the purchase decision. Since accumulators can store volume, we generate a time-expansion $\mathcal{G} = (\mathcal{V}, \mathcal{E})$ of the system graph G by copying it once for every time step [1]. Each edge $(i, t_i, j, t_j) \in \mathcal{E}$ connects vertices $(i, t_i) \in \mathcal{V}$ at time t_i and $(j, t_j) \in \mathcal{V}$ at time t_j . An accumulator is represented by edges in time, connecting one point in time with the next, while the other components are edges in space, representing quasi-static behavior. Binary variables a_{i,t_i,j,t_j} for each edge of the expanded graph allow to deactivate purchased components during operation. The conservation of the volume flow Q_{i,t_i,v,t_v} in space and time is given by

$$\forall v \in \mathcal{V}: \quad \sum_{(i,t_i,v,t_v) \in \mathcal{E}} Q_{i,t_i,v,t_v} \cdot \Delta t = \sum_{(v,t_v,j,t_j) \in \mathcal{E}} Q_{v,t_v,j,t_j} \cdot \Delta t \quad (1)$$

with time step Δt . An additional condition with an adequate upper limit Q_{\max} makes sure that only active components contribute to the volume flow conservation:

$$\forall e \in \mathcal{E}: \quad Q_{i,t_i,j,t_j} \leq Q_{\max} \cdot a_{i,t_i,j,t_j} \quad (2)$$

Another physical constraint is the pressure propagation

$$\forall (i, t_i, j, t_i) \in \mathcal{E}: \quad p_{j,t_i} \leq p_{i,t_i} + \Delta p + M \cdot a_{i,t_i,j,t_i} \quad (3)$$

$$p_{j,t_i} \geq p_{i,t_i} + \Delta p - M \cdot a_{i,t_i,j,t_i} \quad (4)$$

which has to be fulfilled along each edge in each time step, if the component is active. Regarding pumps, the resulting increase of pressure depends on the rotational speed of the pump and on the volume flow that is conveyed, cf. Fig. 1(b). For pipes and valves, pressure loss increasing with the volume flow is observed, cf. Figs. 1(a), 1(c) and 1(d). All of the measured characteristic curves were linearly approximated and included in the model by a convex combination formulation. [5]

4 Experimental Validation

To validate our mathematical model, we consider three test cases with different time-dependent demand profiles. To assess the modeling error, the computed optimal combination of the available components is replicated in an experimental setup, and the settings of the system (e.g. the speed of the used pumps or the valve lift) are adjusted according to the computed optimal variable assignment. Subsequently, we verify if the demand profiles are met in each time step. Moreover, the energy consumption of the setup is measured and the resulting energy costs are calculated and compared to the objective value of the mathematical model.

4.1 The Test Rig

Fig. 2 shows the modular test rig used for validation measurements. It consists of a combination of up to three speed-controlled centrifugal pumps in a row and




Fig. 1 Input data for the model are the measured characteristic curves of the components of the fluid system. Each data point is the mean value of 10,000 samples. The error bars depict the corresponding standard deviation.

an optional acrylic barrel which serves as volume and pressure accumulator. The three pumps differ in their maximum rotating speed (S: 2800 rpm, M: 3400 rpm, L: 4450 rpm) and power consumption. Fig. 1(b) depicts the characteristic curves of pump L. The accumulator has a maximum volume of 50 l and a maximum storable pressure of ≈ 0.2 bar. The barrel can be charged and discharged via a controllable valve, cf. Fig. 1(a). Closing the ball valve allows to charge the accumulator without conveying water to the sink. The volume flow is measured by a magnetic flow meter with a tolerance of $\pm 0.11/\text{min} = \pm 0.006 \text{ m}^3/\text{h}$. Pressure measurements are performed by manometers with a tolerance range of $\pm 0.01 \text{ bar} \approx \pm 0.1 \text{ mH}_2\text{O}$. All data points represent the mean value of 10,000 samples, collected within 10 s.

4.2 Comparison of Optimization Results and Measurements

Three different load profiles are given as an input to the optimization program. We built every calculated first-stage solution on our test rig, set up the control strat-




Fig. 2 The test rig consists of a combination of up to three out of three different speed-controlled centrifugal pumps. An optional accumulator can be used to fulfill the demand at the sink. It can be charged and discharged via a controllable valve.

egy and measured the volume flows at the sink and the power consumption of the pumps. The measurement results are given in Figs. 3 - 5.

The time-varying flow demand of the first test case is between 0.25 m³/h and 0.6 m³/h. It can be fulfilled by pump M and pump L, but not by pump S. As pump M is at a lower price than pump L, the optimal result via MILP is to buy pump M. The measured flow is in good agreement with the demand profile, cf. Fig. 3, if the pump is driven with the predicted control settings. The computed total energy consumption for a recovery period of 10 years is 1.9126×10^3 kWh, corresponding to energy costs of €478.14, and total costs of €923.14. The measured energy consumption for one repetition of the load cycle is $(663.0 \pm 11.2) \times 10^3$ kWh, which sums up to $(1.9369 \pm 0.1117) \times 10^3$ kWh and € (484.23 ± 9.57) within 10 years.

The second test case contains higher flow demands than the first one: 0.4 m³/h to 0.9 m³/h. The optimization result is to use pumps S and M to cover the load. The demanded and measured volume flow rates match, cf. Fig. 4. During a recovery period of 20 years the pumps consume 1.0565×10^4 kWh according to the optimization result, compared to $(1.0765 \pm 0.0239) \times 10^4$ kWh derived from the measurements. This leads to total optimal costs of €3436.27, compared to € (3486.32 ± 59.85) . Pump L could have also been used, but its energy consumption is higher for flow demands around 0.7 m³/h.




Fig. 3 Test case 1. One pump fulfills the load.




Fig. 4 Test case 2. Two pumps fulfill the load.




Fig. 5 Test case 3. One pump in combination with an accumulator fulfills the load.

The flow demands in the third test case range from $0.1 \text{ m}^3/\text{h}$ to $0.8 \text{ m}^3/\text{h}$. The optimal topology consists of pump L, the accumulator and the valve. Pump L cannot convey volume flows as low as $0.05 \text{ m}^3/\text{h}$ in the test rig configuration. The optimization model correctly predicts the usage of the accumulator during time steps with these small demands. The accumulator starts with a positive water level and has already stored energy free of charge. Thus, our MILP guarantees that it is filled to the beginning level until the last time step.

In Fig. 5 the measured data is in satisfying agreement with the time-varying demand. The optimal energy costs are $\text{€}537.57$. Compared to $\text{€}(584.27 \pm 27.91)$ derived from the measurements this corresponds to the highest observed deviation of 8.7 %. For all test cases a delayed step response of around 5 s - 10 s to the changed rotational speed settings is observed.

5 Conclusion

In this paper, we presented a MILP model for a system synthesis problem. We are able to find the best combination out of a set of pumps, valves and accumulators to satisfy a given time-dependent flowrate demand with minimal weighted purchase and energy costs. The predicted topology and operating decisions were validated in an experimental setup for three different load demands. The measured volume flows and the power consumption of the pumps match the predicted values with satisfying accuracy. The observed deviations could be caused by the delayed response of the pumps when changing their speed settings. We plan to investigate the influence of the time step size on the modeling error in a future research project. This will allow us to determine to which degree the components' start-up characteristics and deferred adaptation should be included into our model formulation.

References

- [1] B. Dörig, T. Ederer, P. Hedrich, U. Lorenz, P. F. Pelz, and P. Pöttgen. Technical operations research (TOR) exemplified by a hydrostatic power transmission system. In *9. IFK – Proceedings Vol.1*, 2014.
- [2] P. F. Pelz, U. Lorenz, T. Ederer, S. Lang, and G. Ludwig. Designing pump systems by discrete mathematical topology optimization: The artificial fluid systems designer (AFSD). In *IREC, Düsseldorf, Germany*, 2012.
- [3] P. F. Pelz, U. Lorenz, T. Ederer, M. Metzler, and P. Pöttgen. Global system optimization and scaling for turbo systems and machines. In *ISROMAC-15, Honolulu, USA*, 2014.
- [4] A. Schrijver. *Theory of linear and integer programming*. John Wiley & Sons, 1998.
- [5] J. P. Vielma, S. Ahmed, and G. Nemhauser. Mixed-integer models for nonseparable piecewise-linear optimization: Unifying framework and extensions. *Operations research*, 58(2):303–315, 2010.